Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Hama

Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE

Model identifier: 00176558

Type of light source:

Light source cap-type	GU10	directional:	
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
0,	mption in on- 000 h), rounded est integer	5	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (φuse), refers to the flux 60º), in a wide in a narrow cone	388 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500		
On-mode expressed in W	power (P _{on}),	4,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,53		
for CLS, expre	ndby power (P _{net}) essed in W and second decimal	0,53	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	81		
Outer	Height	70	Spectral power	See image		
dimensions	Width	50	distribution in the	in last page		
without	Depth	50		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	28			
		Chromaticity coordinates (x and y)	0,310 0,330			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,70					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,89	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'_-' : not applicable;

